

MSDS ID: 8061076

---

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

---

PRODUCT PART NUMBER: 8061076  
DESCRIPTION: 7281 WHITE

COMPANY:  
Markem Corporation  
150 Congress Street  
Keene, NH 03431

EMERGENCY RESPONSE NUMBERS:  
Transportation:  
United States: (800) 424-9300  
International: (703) 527-3887(collect)  
Product Safety and Environmental:  
(603) 352-1130

---

2. HAZARDOUS INGREDIENTS

---

COMPONENT	CAS #	PCT(WT)
Neopentyl glycol diglycidyl ether	17557-23-2	1-5
Tributyl phosphate	126-73-8	5-10
Propylene carbonate	108-32-7	1-5
Cycloaliphatic epoxy resin	2386-87-0	10-30

Exposure and physical property information is presented in Section 9. If the total percentage is less than 100, the balance of this product is not considered to be hazardous as defined in the OSHA Hazard Communication Standard (29 CFR 1910.1200).

---

3. HAZARDS IDENTIFICATION

---

EMERGENCY OVERVIEW

HMIS RATING SYSTEM  
Health: 3  
Flammability: 1  
Reactivity: 0  
Protection: B

NFPA RATING SYSTEM  
Health: 3  
Flammability: 1  
Reactivity: 0

POTENTIAL HEALTH CONSIDERATIONS

LIKELY ROUTES OF ENTRY:

Contact; Inhalation; Absorption; Ingestion

TARGET ORGANS:

Respiratory Tract; Eyes; Skin; Liver; Kidneys; Bladder; Nervous System; Lungs;

POTENTIAL IMMEDIATE EFFECTS FROM OVEREXPOSURE

---

### 3. HAZARDS IDENTIFICATION (Cont.)

---

#### EYE CONTACT

Can cause severe eye irritation, tearing and reddening, but not likely to permanently injure eye tissue. Temporary vision impairment (cloudy or blurred vision) is possible.

#### SKIN CONTACT

Can cause severe skin irritation, defatting, and dermatitis. Not likely to cause permanent skin damage.  
Skin Sensitizer! Avoid exposure. If sensitized, repeated exposures will result in skin irritation, even at very low concentrations.

#### SKIN ABSORPTION

Toxic if absorbed through the skin causing systemic damage.

#### INHALATION

Can cause respiratory irritation, dizziness, weakness, fatigue, nausea, headache and possible unconsciousness.

#### INGESTION

Toxic. If swallowed, may cause abdominal discomfort, nausea, vomiting, diarrhea and systemic poisoning.

#### POTENTIAL LONG-TERM EFFECTS FROM OVEREXPOSURE:

#### CANCER INFORMATION

Contains a substance that can cause cancer in laboratory animals at high oral doses. Not a carcinogen according to NTP, IARC, or OSHA.

No IARC cancer hazard information available.

No ACGIH cancer hazard information available.

No NTP cancer hazard information available.

No OSHA cancer hazard information available.

#### REPRODUCTIVE SYSTEM INFORMATION

None of the substances in this product have been shown to cause reproductive system disorders.

#### ADDITIONAL HEALTH HAZARD INFORMATION

Neopentyl glycol diglycidyl ether: This substance was found to be carcinogenic in skin painting tests on mice. This material may be mutagenic based on laboratory tests. A small residual of epichlorohydrin remain and has been shown to produce cancer in lab animals.

Tributyl phosphate: TBP was found not to be neurotoxic either acutely at 1000 mg/kg or after three months of exposure at up to 325 mg/kg/day. Assuming similar absorption of TBP by oral and inhalation routes of exposure and a breathing rate of approximately 170 mL/min, these values are approximately equivalent to inhalation exposures of 4900 mg/cu m acutely and 1590 mg/cu m per day subchronically. The ACGIH TLV (TWA) for TBP is 2.2 mg/cu m. This indicates that a minimum of a 700-fold safety factor exists for TBP as a potential neurotoxin(1). Large doses have been reported to cause dyspnea, weakness, pulmonary edema, and twitching in rats. Chronic inhalation of

---

### 3. HAZARDS IDENTIFICATION (Cont.)

---

large doses can lead to general poisoning with paralysis, urinary bladder hyperplasia, and increased liver weight.(1) Healy, C.E.; Beyrouthy, P.C.; and Broxup, B.R., Am. Ind. Hyg. Assoc J. 56:349-355 (1995).

#### MEDICAL CONDITIONS POTENTIALLY AGGRAVATED BY OVEREXPOSURE

---

### 4. FIRST AID MEASURES

---

#### EYE CONTACT

Immediately flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Get immediate medical attention.

#### SKIN CONTACT

Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists.

#### INHALATION

Remove to fresh air. If not breathing, perform rescue breathing and, if available, have a trained person administer oxygen. Get medical attention immediately.

#### INGESTION

Emergency personnel should be contacted immediately and be provided with this MSDS. For ingestion of small quantities of chemicals, the risk associated with inducing vomiting usually exceeds the poisoning risk.

---

### 5. FIRE FIGHTING MEASURES

---

#### FLAMMABILITY DATA

FLASH POINT: 239 F, 114 C

EXPLOSIVE/FLAMMABILITY LIMITS ESTIMATED FROM INGREDIENTS:

LOWER LIMIT: 1.7 %

UPPER LIMIT: 32.5 %

AUTOIGNITION TEMPERATURE ESTIMATED FROM INGREDIENTS:

770 F, 410 C

#### GENERAL HAZARDS

Material may ignite if heated to temperatures above the flash point in the presence of a source of ignition.

#### EXTINGUISHING MEDIA

Small Fires: Dry chemical, CO<sub>2</sub>, water spray or alcohol-resistant foam. Large Fires: Water spray, fog or alcohol-resistant foam. Move containers from fire area if it can be done without risk. Apply cooling water to containers that are exposed to flames until well after fire is out.

#### FIRE FIGHTING INSTRUCTIONS

Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location. Heat may build pressure and rupture closed containers, spreading fire and increasing risk of burns or injuries.

---

## 5. FIRE FIGHTING MEASURES (Cont.)

---

Use water spray/fog for cooling. Even if material is water soluble, it may not be practical to extinguish fire by water dilution. Notify authorities if liquid enters sewers or other public waters.

### HAZARDOUS COMBUSTION PRODUCTS

carbon dioxide; carbon monoxide; fluorine containing gases; smoke; phosphorus compounds

---

## 6. ACCIDENTAL RELEASE MEASURES

---

### SPILL CLEAN-UP PROCEDURES

Prevent the spread of any spill to minimize harm to human health and the environment. Dike with suitable absorbent material. Wear complete and proper personal protective equipment and ventilate the area.

### HEALTH CONSIDERATIONS AND PROTECTIVE EQUIPMENT

Information on the selection and use of personal protective equipment is found in Section 8 of this MSDS. Personal protective equipment needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; material spilled, quantity, the area in which it occurred and the expertise of employees in the area responding to the spill. Never exceed any occupational exposure limits and consider that the evaporation of volatile solvents can lead to the displacement of air creating an environment that can cause asphyxiation.

---

## 7. HANDLING AND STORAGE

---

### HANDLING

Avoid contact with material, avoid breathing vapors, use only in a well ventilated area.

### STORAGE

Store in a cool, dry place. Isolate from incompatible materials.

---

## 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

---

### ENGINEERING CONTROLS

Local exhaust ventilation or other engineering controls are normally required when handling or using this product to keep exposure to airborne contaminants below the TLV, PEL, or other recommended exposure limit and/or maintain operator comfort.

Facilities storing or using this material should be equipped with an eyewash and safety shower.

### RESPIRATORY PROTECTION

If air monitoring indicates airborne concentrations at or above the limits, or symptoms of inhalation over-exposure occur, a respiratory protection program may be required. Engineering controls to reduce the exposure below acceptable limits are usually preferable to a respirator program.

---

## 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION (Cont.)

---

**EYE PROTECTION**

Chemically resistant safety glasses with side shields must be worn when handling this product. Further eye protection such as chemical splash goggles and/or face shield must be worn when the possibility exists for eye contact due to splashing or spraying liquid or airborne particles. Contact lenses should not be worn. An eye wash station should be available.

**SKIN PROTECTION**

Prevent skin contact by wearing gloves and other protective equipment. Inspect gloves for chemical break-through and replace if detected. Clean protective equipment thoroughly after each use. Do not remove from workplace. An emergency shower in the area is recommended. Appropriate gloves to be used for MARKEM products that are mixtures have not been determined. Glove type(s) for ingredients present at 10% or more (if known) are:  
Polyvinyl chloride,

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES - PRODUCT

---

APPEARANCE: Liquid, semi-solid, or solid  
 COLOR: See description in Section 1.  
 ODOR: Mild solvent odor  
 SPECIFIC GRAVITY(g/ml): 1.75  
 PERCENT VOLATILE: 11  
 VOC CONTENT(lb/gal): Not determined  
 VAPOR PRESSURE (Pa): Not determined  
 BOILING PT OR RANGE(F): ND  
 pH: NA  
 VISCOSITY: ND  
 VAPOR DENSITY: Heavier than air  
 FREEZING POINT(F): ND  
 EVAPORATION RATE: <0.01 (n-Butyl acetate = 1)

---

### 9.1 EXPOSURE, PHYSICAL AND CHEMICAL PROPERTIES FOR COMPONENTS

---

COMPONENT	ACGIH		OSHA	
	TWA\CEIL	STEL	TWA	CEIL
17557-23-2	NE	NE	NE	NE
126-73-8	0.2 ppm	NE	0.2 ppm	NE
108-32-7	NE	NE	NE	NE
2386-87-0	NE	NE	NE	NE

  

COMPONENT CAS NUMBER	SPECIFIC GRAVITY	EVAP RATE N-BUTYL ACETATE=1	WATER SOLUBILITY Weight %	VAPOR PRESSURE mmHg at F
126-73-8	0.980	<0.01	Negligible;	7.3@302F
108-32-7	1.207	0.5-2	Low;	10-24%.03@20
2386-87-0	1.175	ND	ND	ND

---

## 10. STABILITY AND REACTIVITY

---

### STABILITY

Stable under normal conditions.

### CONDITIONS TO AVOID

Elevated temperatures in combination with sparks, open flames, or other sources of ignition.

### INCOMPATIBILITY

None Known; acids; caustics (bases); strong oxidizing agents;

### HAZARDOUS DECOMPOSITION PRODUCTS

carbon dioxide; carbon monoxide; fluorine containing gases; smoke; phosphorus compounds

---

## 11. TOXICOLOGICAL INFORMATION

---

Neopentyl glycol diglycidyl ether:

Oral LD50 rat: 4500 mg/kg

Tributyl phosphate:

Acute toxicity:

Oral LD50 rat: 1390 mg/kg, Effect: kidney, ureter, bladder (changes in tubules)

Inhalation LC50 rat: 28 gm/m<sup>3</sup>/1H

Eye rabbit: 500 mg, Effect: Severe

Propylene carbonate

LD50 (oral, rat): 29 g/kg

LD50 (oral, mouse): 20.7 g/kg

LD50 (dermal, rabbit): 24 g/kg

---

## 12. ECOLOGICAL INFORMATION

---

No information available.

---

## 13. DISPOSAL CONSIDERATIONS

---

Dispose of in accordance with all federal, state, local or provincial regulations.

---

## 14. TRANSPORT INFORMATION, DOT and IATA:

---

DOT & IATA: NOT RESTRICTED

---

15. REGULATORY INFORMATION

---

Those ingredients appearing on the following list that do not appear in Section 2 are present at <0.1% for carcinogens, <1% for other hazardous substances, or are not considered hazardous in this product.

UNITED STATES OF AMERICA

FEDERAL REGULATIONS

CERCLA: The following components have CERCLA reportable quantities:

CASRN	DESCRIPTION	CERCLA RQ	WEIGHT%
-------	-------------	-----------	---------

None

RCRA: The following components are subject to RCRA land disposal restrictions:

CASRN	DESCRIPTION
-------	-------------

None

SARA TITLE III

SECTION 302 Extremely Hazardous Substances (EHS)

CASRN	DESCRIPTION
-------	-------------

None

SECTION 311/312 Community Right to Know

CASRN	DESCRIPTION
-------	-------------

None

SARA HAZARD CATEGORY INFORMATION

FIRE: NO

SUDDEN RELEASE OF PRESSURE: NO

REACTIVE: NO

IMMEDIATE (ACUTE) HEALTH HAZARD: NO

DELAYED (CHRONIC) HEALTH HAZARD: NO

SECTION 313 Toxic Chemical Release Inventory Reporting (TRI)

CASRN	DESCRIPTION
-------	-------------

None

TSCA

SECTION 8(b) Inventory: All chemicals in this product appear in the inventory or are exempt from the listing requirements.

SECTION 12(b) Export: The following chemicals are subject to export reporting

CASRN	DESCRIPTION
126-73-8	TRIBUTYL PHOSPHATE

STATE REGULATIONS

CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT (PROPOSITION 65)

The following chemical(s) in this product are known to the State of California to cause cancer:

CASRN	DESCRIPTION	WGT%
71-43-2	BENZENE	<0.001
106-89-8	EPICHLOROHYDRIN	<0.001
75-21-8	ETHYLENE OXIDE	<0.001
123-91-1	1,4-DIOXANE	<0.001

The following chemical(s) in this product are known to the State of California to be hazards to reproductive health:

CASRN	DESCRIPTION	WGT%
71-43-2	BENZENE	<0.001

MASSACHUSETTS Right to Know Law

CASRN	DESCRIPTION	%
126-73-8	TRIBUTYL PHOSPHATE	5-10

NEW JERSEY Right to Know Law

CASRN	DESCRIPTION	%
126-73-8	TRIBUTYL PHOSPHATE	5-10

---

---

15. REGULATORY INFORMATION (Cont.)

---

---

PENNSYLVANIA Right to Know Law		
CASRN	DESCRIPTION	%
126-73-8	TRIBUTYL PHOSPHATE	5-10

---

---

16. OTHER INFORMATION

---

---

Note: A CAS number in the form TSXXXX-XX-X is a trade secret.

NA= Not applicable

ND= Not determined

TS= Trade secret

MSDS prepared by Richard C. Berry

This information is offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is made. The recommended industrial hygiene and safe handling practices are believed to be generally applicable, however each user must review the recommendations and determine the suitability for their intended use.