

RELIABILITY MONITOR

PRODUCT	MONITOR DATE	DATE CODE	ASSEMBLY FACILITY	ASSEMBLY LOT NO	PROCESS TYPE	PACKAGE TYPE
DS1000M-25	Nov-96	9642 E3	OMEDATA	DD623657AGA	1.2μ NITRIDE	08 PDIP

STRESS/JOB NO.

READPOINT (Sample Size/No. of Fails)

Infant / High Voltage Life 125°C, 7.0 V. P-18586, P-18645	<u>48 Hr</u> 231/0	<u>336 Hr</u> 77/0	<u>1KHr</u>	<u>*Failure Rate</u>
---	-----------------------	-----------------------	-------------	----------------------

*Chi Squared Method, 60% C. L., 55°C & 5.5V; Temperature Derating: Ea = 0.7 ev; Voltage Derating B = 1.0

Temp Cycle -55°C to +125°C P-18646	<u>300 ~</u> 39/0	<u>1K ~</u>	<u>Cum %</u>
--	----------------------	-------------	--------------

Biased Moisture 85°C/85% RH, 5.5 V. P-18647	<u>274 Hr</u> 77/0	<u>959 Hr</u>	<u>Cum %</u>
---	-----------------------	---------------	--------------

Autoclave 121°C/100% RH, 2 Atmos P-18648	<u>96 Hr</u>	<u>Cum %</u>
--	--------------	--------------

Failure Mode

Failure Analysis