

RELIABILITY MONITOR REPORT
FOR

Cartridge Package

Dallas Semiconductor

4401 South Beltwood Parkway
Dallas, TX 75244-3292

This Report was prepared by
Dallas Semiconductor Reliability Engineering

Summary:

The data in the tables that follow was generated as the result of an on-going Package Reliability Monitor. The assemblies covered by this package monitor are:

ASSY SITE	PINS	PACKAGE		
Consonic T	3	Cartridge	Dallas	0 Cartridge
Dallas	3	Cartridge	Fastech	2 Cartridge
Fastech	3	Cartridge	Fastech	2 Cartridge (Pb-Free)
Fastech	2	Cartridge w/Chip on Board	Fastech	2 Cartridge w/Flip Chip
Hana	2	Cartridge w/Chip on Board		

Note: Due to the nature of the construction on this assembly, there is no operating life data collected

The reliability data follows. At the start of this data is a description of the assembly vehicle used to generate this reliability data. The next section is the detailed reliability data for each stress. The reliability data section includes the latest data available. This report covers data between 01/04 and 9/30/05 .

Assembly Information:

Package Type: Cartridge
 Flammability: UL 94-V0
 Moisture Sensitivity (JEDEC J-STD20A)
 Date Code Range: 0435 to 0511

STORAGE LIFE

DESCRIPTION	DATE CODE	TEST VEHICLE	CONDITION	READPOINT	QUANTITY	FAILS	FA NO
STORAGE LIFE	0435	DS29020	85 C	336 HRS	77	0	
STORAGE LIFE	0504	DSQ33G4	85 C	1000 HRS	77	0	
STORAGE LIFE	0504	DSQ33G4	85 C	1000 HRS	77	0	
STORAGE LIFE	0504	DSQ33G4	85 C	1000 HRS	77	0	
Total:						0	

TEMPERATURE CYCLE

DESCRIPTION	DATE CODE	TEST VEHICLE	CONDITION	READPOINT	QUANTITY	FAILS	FA NO
TEMP CYCLE	0435	DS29020	-40 TO 85C	400 CYS	77	0	
TEMP CYCLE	0504	DSQ33G4	-40 TO 85C	1000 CYS	77	0	
TEMP CYCLE	0504	DSQ33G4	-40 TO 85C	1000 CYS	77	0	
TEMP CYCLE	0504	DSQ33G4	-40 TO 85C	1000 CYS	77	0	
TEMP CYCLE	0511	DS29020	-40 TO 85C	400 CYS	77	0	
Total:						0	

UNBIASED MOISTURE RESISTANCE

DESCRIPTION	DATE CODE	TEST VEHICLE	CONDITION	READPOINT	QUANTITY	FAILS	FA NO
MOISTURE SOAK	0435	DS29020	85 C/85% R.H.	274 HRS	77	0	
MOISTURE SOAK	0504	DSQ33G4	60C/90% R.H.	1000 HRS	77	0	
MOISTURE SOAK	0504	DSQ33G4	60C/90% R.H.	1000 HRS	77	0	

MOISTURE SOAK	0504	DSQ33G4	60C/90% R.H.	1000 HRS	77	0
MOISTURE SOAK	0511	DS29020	85 C/85% R.H.	274 HRS	77	0
Total:						0

Assembly Information:

Package Type: Cartridge (Pb-Free)
 Flammability: UL 94-V0
 Moisture Sensitivity (JEDEC J-STD20A) Level 1
 Date Code Range: 0451 to 0451

STORAGE LIFE

DESCRIPTION	DATE CODE	TEST VEHICLE	CONDITION	READPOINT	QUANTITY	FAILS	FA NO
STORAGE LIFE	0451	DSQ33G1+ M01	85 C	1000 HRS	77	0	
STORAGE LIFE	0451	DSQ33G1+ M01	85 C	1000 HRS	77	0	
STORAGE LIFE	0451	DSQ33G1+ M01	85 C	1000 HRS	77	0	
Total:						0	

TEMPERATURE CYCLE

DESCRIPTION	DATE CODE	TEST VEHICLE	CONDITION	READPOINT	QUANTITY	FAILS	FA NO
TEMP CYCLE	0451	DSQ33G1+ M01	-40 TO 85C	1000 CYS	77	0	
TEMP CYCLE	0451	DSQ33G1+ M01	-40 TO 85C	1000 CYS	77	0	
TEMP CYCLE	0451	DSQ33G1+ M01	-40 TO 85C	1000 CYS	77	0	
Total:						0	

UNBIASED MOISTURE RESISTANCE

DESCRIPTION	DATE CODE	TEST VEHICLE	CONDITION	READPOINT	QUANTITY	FAILS	FA NO
MOISTURE SOAK	0451	DSQ33G1+ M01	60C/90% R.H.	1000 HRS	77	0	
MOISTURE SOAK	0451	DSQ33G1+ M01	60C/90% R.H.	1000 HRS	77	0	
MOISTURE SOAK	0451	DSQ33G1+ M01	60C/90% R.H.	1000 HRS	77	0	
Total:						0	