

**RELIABILITY MONITOR REPORT  
FOR**

**uSOP Package**

**Dallas Semiconductor**

**4401 South Beltwood Parkway  
Dallas, TX 75244-3292**

**This Report was prepared by  
Dallas Semiconductor Reliability Engineering**

**Summary:**

The data in the tables that follow was generated as the result of an on-going Package Reliability Monitor. The specific assemblies included in this package monitor are:

ASSY SITE	PINS	PACKAGE		
Unisem	8	uSOP (Pb-Free)	UTL (NSEB) UTAC	8 uSOP (Pb-Free)

The calculated failure rate for this assembly is:

**FAILURE RATE: MTTF (YRS): 10575 FITS: 10.8**

The parameters used to calculate this failure rate are as follows:

**Cf: 60% Ea: 0.7 Tu: 25 °C**

The reliability data follows. At the start of this data is a description of the assembly vehicle used to generate this reliability data. The next section is the detailed reliability data for each stress. The reliability data section includes the latest data available. This report covers data between and

---

**Assembly Information:**

Package Type: uSOP (Pb-Free)  
Flammability: UL 94-V0  
Date Code Range: 0717 to 0723

---

**OPERATING LIFE**

DESCRIPTION	DATE CODE	TEST VEHICLE	CONDITION	READPOINT	QUANTITY	FAILS	FA NO
HIGH TEMP OP LIFE	0717	DS2704R	125C, 5.5 VOLTS	1000 HRS	45	0	
HIGH TEMP OP LIFE	0723	DS1372	125C, 5.5 VOLTS	1000 HRS	45	0	
				<b>Total:</b>		<b>0</b>	

**FAILURE RATE: MTTF (YRS): 10575 FITS: 10.8**